

## Gas Analyzer GAE1 CH<sub>4</sub>



The gas analyzer GAE is a non-dispersive infrared-photometer (NDIR). It records the absorption of infrared rays, caused by the measuring gas. The wavelengths of the absorption bands characterize the type of gas, whilst the intensity of the absorption is a measurement for the concentration of the measuring components.

## **Technical Data**

Range: 0-5, 0-10, 0-50, 0-100 Vol% CH<sub>4</sub>

Accuracy: +/- 2% FS (Full scale)

Pressure Dependence: < 2% FS / 10hPa (non compensated)

< 0,2% FS / 10hPa (compensated, optional)

Lower Detection Limit: < 1% FS

Response Time: 10 Sec

Temperature Range: 5-45 ℃

Humidity Range: 0-100% rel. Humidity (non condensing)

Measurig gas flow: 10 - 90 l/h

Power Supply: 24-30VDC (electronic stabilized)

Power Consumption: < 200mA

Analoque output: 4-20mA (non isulated)

Max Load mA-Output: < 100 Ohm

Dimensions: Weight 107mm (1/4 19"), Deep: 200mm

NUK NENNING UND KRUMM GmbH

Mangenberger Str. 379, D-42655 Solingen

www.nuk-gmbh.de

Telefon: +49 212 - 2 68 11 93 Telefax: +49 212 - 2 68 11 95

email: <u>info@nuk-gmbh.de</u>